

Not PI APPLiA certified

20003821
KA70KT0EG


	Hisense
	Air conditioner - indoor unit
	6946087393809
	Not PI APPLiA certified
Unite type	Internal unit
Type of internal unit	Wall mounted
Remote control	Remote
Wi-Fi operation	Integrated
Recommended are for cooling (m ²)	26-38
Operating temperature range in heating mode (°C)	-22- 24
Operating temperature range in cooling mode (°C)	-15 - 50
Temperature setting range (°C)	16-30
Compact design	Yes
Manual switch	Yes
Operating mode	Inverter
Refrigerant	R32
Louver Position Memory Function	Yes
2-way draining	Left or right
EER	3,5
Energy efficiency class - heating	A++
Speed level of outdoor ventilator	3
Speed level of indoor ventilator	7
Cooling power (Btu/h)	24000
Heating power (Btu/h)	24000
Remote control as room thermostat	Yes
Hidden LED display	Yes
Dimmer	Yes
Self-diagnosis	Yes
Auto indoor fan	Yes
Heating design load (Pdesignh)-average heating season	5 kW
Declared capacity (Pdh(Tj))-average heating season	5 kW
Cooling capacity	7 kW

Dehumidification capacity	2,2 l/h
Diameter of condensing pipe	18 mm
4 in 1 - vitamin C + catechin + silver + HEPA + active carbon	Yes
Automatic activity	Yes
Auto restart	Yes
Self-cleaning function	Yes
Freeze protection	Yes
Turbo	Yes
Cooling	Yes
Heating	Yes
Dehumidification	Yes
Ventilation	Yes
Timer 24 h	Yes
Voice control	Yes
Hinano generator	Yes
Silent operation for more comfort	Yes, 19dB(A)
Voltage (V)	220-240 V
Minimum audio power	63 dB(A)re 1 pW
Heating power	7500 W
Stand-by power consumption	1 W
Frequency	50 Hz
Cooling power	7000 W
Refrigerant charge	1,5 kg
Minimum sound pressure	36 dB(A)2x10-5Pa
Maximum sound pressure	45 dB(A)2x10-5Pa
Connecting power at heating	2100 W
Connecting power at cooling	2000 W
Outdoor Unit Chassis Heating	Yes
Air flow - min	750 m³
Air flow - max	1100 m³
Diameter of liquid pipe	9,53 mm
Diameter of gas pipe	15,88 mm
Maximum pipe length	20 m
Maximum height difference	15 m
Nominal current - cooling	8,9 amp
Nominal current - heating	9,4 amp
Ratio SEER - cooling	7,9
Ratio SCOP - heating	4,6
COP	3,57
Minimum sound pressure	36 dB(A)2x10-5Pa
Maximum sound pressure	45 dB(A)2x10-5Pa
Dimensions (W×H×D)	100,8 × 32,5 × 21,7 cm
Dimensions of packed product (W×H×D)	112 × 39 × 31,5 cm
Net weight	12 kg
Gross weight	14,5 kg
Stand-by power consumption	1 W
Nominal current of fuse	5 amp
Product code	20003821
EAN code	6946087393809